(19) World Intellectual Property Organization

International Bureau





(43) International Publication Date 9 June 2005 (09.06.2005)

PCT

(10) International Publication Number WO 2005/052892 A1

(51) International Patent Classification⁷: H05B 33/10, G02F 1/1333

G09F 9/00,

--,

(21) International Application Number:

PCT/JP2004/017522

(22) International Filing Date:

18 November 2004 (18.11.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

2003-399978

28 November 2003 (28.11.2003)

(71) Applicant (for all designated States except US): SEMI-CONDUCTOR ENERGY LABORATORY CO., LTD. [JP/JP]; 398, Hase, Atsugi-shi, Kanagawa 2430036 (JP).

(72) Inventors; and

(75) Inventors/Applicants (for US only): YAMASHITA, Akio [JP/JP]; c/o Semiconductor Energy Laboratory Co., Ltd., 398 Hase, Atsugi-shi, Kanagawa 2430036 (JP). FUKUMOTO, Yumiko [JP/JP]; c/o Semiconductor Energy Laboratory Co., Ltd., 398 Hase, Atsugi-shi, Kanagawa 2430036 (JP). GOTO, Yuugo [JP/JP]; c/o Semiconductor Energy Laboratory Co., Ltd., 398 Hase, Atsugi-shi, Kanagawa 2430036 (JP).


- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: METHOD OF MANUFACTURING DISPLAY DEVICE



(57) Abstract: To provide a method of manufacturing a display device having an excellent impact resistance property with high yield, in particular, a method of manufacturing a display device having an optical film that is formed using a plastic substrate. The method of manufacturing a display device includes the steps of: sequentially forming a metal film, an oxide film, and an optical filter on a first substrate; separating layers including the optical filter from the first substrate; attaching layers including the optical filter to a second

substrate; forming a layer including a pixel on a surface of a third substrate; attaching the layer including the pixel to a fourth substrate; and attaching layers including the optical filter to another surface of the third substrate.

VO 2005/052892 A1